

# SDT2

Electronic Digital Theodolite



CE



*Building the Future with*  
**Accuracy  
& Precision**

# SDT2

## Electronic Digital Theodolite

### Data Specifications

---

#### Telescope

Image	Erect
Magnification	30x
Effective Aperture	47mm
Resolving Power	3.75"
Field of View	1°30' (26m/1000m)
Min. Focus	1.5m
Stadia Ratio	100
Tube Length	169mm

---

#### Angle Measurement

Method	Absolute Encoding
Diameter	79mm
Min. Reading	1", 5", 10"
Measuring Unit	360°, 400gon
Vertical Angle 0°	Zenith 0°, Horizontal 0°
Accuracy	2"

---

#### Vial

Plate Vial	30"/2mm
Circular Vial	8'/2mm

---

#### Compensator

Electronic Tilt Sensor	Vertical Compensation
Compensation Range	±3"
Resolving Power	6"

---

#### Display

Type	Dual Face LCD
------	---------------

---

#### On-board Battery

Power Resource	Rechargeable Li-ion battery
Voltage	DC 7.4V
Operation Time	BDC 1600mAh(About 20 hours)

---

#### Laser

Length of the Wave	635nm
Power	10mW
Effective Range	150m
Position Error	≤5"
Power	DC 3.3V

---

#### General

Laser Plummet	Red laser, Class II
Operating Temperature	-20°C - 45°C
Dimension	180mm x 166mm x 355mm
Weight	6.5kg



**Headquarters:**  
Datavägen 21B  
SE-436 32 Askim, Sweden  
info@satlab.com.se

**Regional Offices:**  
Warsaw, Poland  
Jičín, Czech Republic  
Ankara, Turkey  
Scottsdale, USA  
Singapore  
Hong Kong  
Dubai, UAE

[www.satlab.com.se](http://www.satlab.com.se)

